



ULTRA SEAT CORPORATION

# HIGH & MEDIUM BACK SEAT COVER KIT INSTALLATION GUIDE

High Back Shown in Instructions

**1.** Remove arms and headrest according to your seat instructions. If no arms or headrest are present, move to Step 3a.



**2.** Slide the headrest cover over your existing headrest, tuck in and secure the velcro tabs. Set aside while you install the back cover.



**3a.** Turn the back cover partially inside out leaving enough to grasp and pull over the upper portion of your seat.



**3b.** Place the unturned portion of the cover over the top of the upper area of your seat back and start rolling/pulling it down over your seat. Making sure to adjust and align your seams along the way.

**4.** On the front portion of the back cover push the velcro strip through the gap between back of the seat and seat cushion. Pull tight and secure velcro edges together.



**5.** Reinstall your seat arms and headrest according to your seat instructions.



**6.** Slip the seat cover over your seat cushion. Push the back of the cover with the elastic cord loops through the gap between the back of the seat and seat cushion.



**7.** Pull the elastic cord with "S" hook around each side of the seat and secure to the elastic loop that you pushed through previously.



Note: If you find the lower portion of your seat cover loose after installation you may need to tighten the elastic cord with the "S" hooks. To do this, simply untie the knot that holds the "S" hook in place and slide further down the cord and re-tie the knot.



Phone: 1-800-667-7328 · Fax: 1-888-667-7328  
WWW.ULTRASEAT.COM

DISTRIBUTION CENTERS ALL  
ACROSS NORTH AMERICA